

10/529857

Rec'd PCT 31 JAN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/016040 A1

- (51) International Patent Classification⁷: **H04R 25/00**
- (21) International Application Number:
PCT/EP2003/005648
- (22) International Filing Date: 28 May 2003 (28.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02 017 613.7 5 August 2002 (05.08.2002) EP
- (71) Applicant (for all designated States except US): **SONY ERICSSON MOBILE COMMUNICATIONS AB** [SE/SE]; Nya Vattentornet, S-221 88 Lund (SE).


- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **LECHNER, Thomas** [DE/DE]; Schlehenring 115, 85551 Kirchheim (DE).
- (74) Agent: **KÖRBER, Martin**; Mitscherlich & Partner, Sonnenstrasse 33, 80331 München (DE).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SIGNAL STRENGTH INFORMATION DEPENDENT CONTROL OF SMALL ELECTRODYNAMIC TRANSDUCERS IN AUDIO SYSTEMS



(57) Abstract: A control circuit for a signal strength information dependant frequency response adaptation of an audio signal for an electrodynamic transducer (4), with a signal strength information determination means (2, 6) for determining a signal strength information according to the level of the audio signal, and a modifying means (3) for frequency selectively modifying the audio signal in response to the signal strength information such, that the electrodynamic transducer (4) converts the audio signal into a low distortion sound signal for high levels of an audio signal and with a flat frequency response for low levels of an audio signal, whereby

a lower frequency range of the audio signal is modified with a gain different to a gain of a higher frequency range of the audio signal and a frequency separating the lower frequency range from the higher frequency range is shifted towards higher values for an increasing level of the audio signal and towards lower values for a decreasing level of the audio signal. The present invention further proposes a mobile telecommunication terminal with an accordingly designed control circuit.

WO 2004/016040 A1